



Product Submittal Sheet

Tech Support / Sales: 800-334-1676
www.tamlyn.com

XtremeTrim® Standard J Mold

07 46 00 (SIDING ACCESSORIES)

DESIGN FEATURES

Provides a clean finish at openings, edges of panels or planks and at material transitions. Specifically designed to work in conjunction with other XtremeTrim® profiles.

MATERIAL

6063-T5 .050" ± .005 extruded aluminum alloy with proprietary coating that protects against harsh weather conditions and allows for paint adhesion.

FINISH


Unless specified all XtremeTrim® items are provided in primed finish. Also available in popular siding/soffit colors in standard face only color match or full coverage CoastalColorCoating™. Clear Anodized is stocked and custom anodized is available (minimums apply).

NOTE

Do not install XtremeTrim® Standard J mold upside down on horizontal applications where the exterior flange can catch water.



Standard J Mold



ITEM ID	"A"	"B"	"C"	SIDING SIZE
JMH51610	3/8"	3/8"	1-1/16"	5/16"
JMH71610	3/8"	15/32"	1-1/16"	7/16"
JMH5810	3/8"	5/8"	1-1/4"	5/8"
JMH3410	5/8"	3/4"	1-1/8"	3/4", 5/16" Lap
JMH110	3/8"	1"	1-1/4"	1"
JMH15	3/8"	1-1/2"	1-3/8"	1-1/2"

All parts are 10' Length unless otherwise indicated

Green Building and LEED

Tamlyn products can earn or contribute to credits in categories MR 4.1 and MR 4.2. These credits require a minimum percentage of the value of the building materials to be recycled. Tamlyn products are typically made from 75-100% post industrial and post consumer scrap.

For more details and LEED letters contact Technical Support at 800-334-1676.

© 2017 R.H. Tamlyn & Sons, LP

Project Information

Name:
Address:

Contractor Information

Name:
Contact:
Phone:
Fax:

Architect Information

Name:
Contact:
Phone:
Fax: