



# Product Submittal Sheet

Tech Support / Sales: 800-334-1676  
www.tamlyn.com

## XtremeTrim® Basic J Mold

### 07 46 00 (SIDING ACCESSORIES)

#### DESIGN FEATURES

Provides a clean finish at openings, edges of panels or planks and at material transitions. True size designed as an independent profile. Use as a closure/cap piece only.

#### MATERIAL

6063-T5 .037" ± .005 extruded aluminum alloy with proprietary coating that protects against harsh weather conditions and allows for paint adhesion.

#### FINISH


Unless specified all XtremeTrim® items are provided in primed finish. Also available in popular siding/soffit colors in standard face only color match or full coverage CoastalColorCoating™. Clear Anodized is stocked and custom anodized is available (minimums apply).

#### NOTE

Do not install XtremeTrim® J mold on horizontal applications where the exterior flange can catch water.



Basic J Mold



ITEM ID	"A"	"B"	"C"	SIDING SIZE
JMS5168	1"	5/16"	3/8"	5/16"
JMS7168	1"	7/16"	3/8"	7/16"
JMS588	1"	5/8"	3/8"	5/8"

All parts are 8' Length unless otherwise indicated

#### Green Building and LEED

Tamlyn products can earn or contribute to credits in categories MR 4.1 and MR 4.2. These credits require a minimum percentage of the value of the building materials to be recycled. Tamlyn products are typically made from 75-100% post industrial and post consumer scrap.

For more details and LEED letters contact Technical Support at 800-334-1676.

© 2017 R.H. Tamlyn & Sons, LP

#### Project Information

Name:  
Address:

#### Contractor Information

Name:  
Contact:  
Phone:  
Fax:

#### Architect Information

Name:  
Contact:  
Phone:  
Fax: